

Alloy Hollow Tine - .750MT x 5.750L x .570OD R108-9133





Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Replaces

Toro

108-9133

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow
B - Tine Mounting	.750 in (19mm)
Dia.	
C - Tine Length	5.75 in (146mm)
D - Tine Tip Outside	.570 in (14.5mm)
(Hole) Dia.	
E - Tine Tip Inside	.400 in (10.2mm)
(Core) Dia.	
F - Tine Wall	.058 in (1.5mm)
Thickness	

Fits Models

Toro Fairway Aerator Toro ProCore 1298 Toro ProCore 440 Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880

O.J. Company 294 Rang St-Paul Sherrington, JOL 2N0 450-247-2758 https://ojcompagnie.rrproducts.com/





Toro ProCore 648s

O.J. Company 294 Rang St-Paul Sherrington, JOL 2NO 450-247-2758 https://ojcompagnie.rrproducts.com/