

Alloy Hollow Side-Eject Tine - .750MT x 4.750L x .470OD



R108-9159



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

Toro 108-9159

Specifications

Manufacturer R&R Products

A - Tine Type Alloy Hollow Side-Eject

B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 4.75 in (121mm)
D - Tine Tip Outside .470 in (11.9mm)

(Hole) Dia.

E - Tine Tip Inside .300 in (7.6mm)

(Core) Dia.

F - Tine Wall .058 in (1.5mm)

Thickness

Savings Volume Buy

Fits Models

Toro Fairway Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

O.J. Company294 Rang St-Paul Sherrington, J0L 2N0

https://ojcompagnie.rrproducts.com/



Alloy Hollow Side-Eject Tine - .750MT x 4.750L x .470OD



R108-9159

T	D	C 10-
I ()r()	ProCore	naxs

O.J. Company 294 Rang St-Paul Sherrington, JOL 2NO 450-247-2758

https://ojcompagnie.rrproducts.com/