



Alloy Machined Side-Eject Tine - .375MT x 5.000L x .650OD R108-9294



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

Toro 108-9294

Specifications

| | |
|----------------------------------|---------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Machined Side-Eject |
| B - Tine Mounting Dia. | .375 in (9.5mm) |
| C - Tine Length | 5 in (127mm) |
| D - Tine Tip Outside (Hole) Dia. | .650 in (16.5mm) |
| E - Tine Tip Inside (Core) Dia. | .500 in (12.7mm) |
| F - Tine Wall Thickness | .065 in (1.7mm) |

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660

O.J. Company

294 Rang St-Paul Sherrington, J0L 2N0
450-247-2758

<https://ojcompagnie.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .375MT
x 5.000L x .650OD**
R108-9294



Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

O.J. Company

294 Rang St-Paul Sherrington, J0L 2N0
450-247-2758

<https://ojcompagnie.rrproducts.com/>