

6000-PRO Shrub Head







Details

-The 6000 Pro series rotors are constructed of high impact plastic and all internal metal parts are made of stainless steel. -3/4" (2 cm) inlet -No tools are required to adjust the arc from 40 - 360 degrees by using the easy to use Click-Set disc. -This series comes with 8 interchangeable nozzles with a discharge range between 1.0 - 9.5 gpm (0.23 - 2.16 m3/hr). There is also a low angle nozzle tree available. -All models come with a rubber protective cap and an optional vandal resistant retaining screw. -The built in slip clutch protects the gears and motor from damage when adjusting for a part circle. If the rotor is manually moved out of position it will automatically reset to the defined pattern. -NIR2 (Nozzle Insertion / Radius Reduction) eliminates the need to remove the cap while fine tuning the radius and inserting the nozzle. -6000 comes in many various styles: shrub head version, heavy duty stainless version, 12" (30,5 cm) high pop version, anti-drain valve (ADV) version and the standard version.

Specifications

Manufacturer Weathermatic

Body Height 7.5 in Cap Diameter 2.875 in Exposed Cap 1.875 in

Diameter

Inlet Size 3/4 in Maximum Pressure 75 psi Pop-up Height 4 in

Quick Coupling Valve Yellow locking cover

Cap Type

Screen Mesh .045 sq in Spinkler Flow 1.0 - 9.5 gpm Spray Trajectory 25 degrees Sprinkler Operating 20 - 65 psi

Range

O.J. Company 294 Rang St-Paul Sherrington, J0L 2N0 450-247-2758

https://ojcompagnie.rrproducts.com/



6000-PRO Shrub Head RGW6001



Replacement Parts

RGW6095 6090 Low Angle 13

Degree Trajectory Nozzle For 6000 Series

Only

RGW77576 6000 Pro Series 25

Degree Trajectory Nozzle Bag of 10

O.J. Company 294 Rang St-Paul Sherrington, JOL 2N0 450-247-2758

https://ojcompagnie.rrproducts.com/