

Alloy Hollow Side-Eject Tine - .750MT x 5.550L x .6700D R201594





Details

Manufactured from special high carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear resistant tine.

Specifications

| Manufacturer | R&R Products |
|----------------------|-------------------------|
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting | .750 in (19mm) |
| Dia. | |
| C - Tine Length | 5.55 in (141mm) |
| D - Tine Tip Outside | .670 in (17mm) |
| (Hole) Dia. | |
| E - Tine Tip Inside | .500 in (12.7mm) |
| (Core) Dia. | |
| F - Tine Wall | .072 in (1.8mm) |
| Thickness | |
| Savings | Volume Buy |
| | |

Fits Models

John Deere Aercore 1000 John Deere Aercore 1500 John Deere Aercore 2000 John Deere Aercore 800 Ryan GA30

O.J. Company 294 Rang St-Paul Sherrington, JOL 2N0 450-247-2758 https://ojcompagnie.rrproducts.com/